

Revolutionary in-line twisting system



- **In-line production:** TWISTUP combines two production processes in a single pass, saving the time and money involved in moving all the bobbins from one machine to the next.
- **Fully compatible with your current machinery.** No need for pre-installation. Automatic synchronisation to the speed of the next process.
- **Modular machine:** The 3-spindle modules adapt to any type of process and offer maximum flexibility.
- **Maximum spindle speed:** 7.000 rpm mechanics.
- **All changes made directly on screen.**
- **Automatic synchronisation:** TWISTUP detects the yarn speed in the following process and adapts automatically.
- **Length counter-warning light:** the light comes on before the bobbin is finished to minimise stop times.
- **Twisting ranges available:** 0-999 twist/metre, S or Z.
- **Feed bobbins of up to 450 mm height and 250 mm diameter.**
- **Twist quality:** automatic self-control and adjustment system to ensure perfect twisting.

Technical Features

TECHNICAL FEATURES	units	TUP-FG
Number of spindles per module	---	3
Max. Number of spindles	---	Unlimited
Feed Speed	m/min	Automatic synchronisation to the speed of the next process
Max. Mechanical spindle speed	rpm	7.000
Power supply	---	220 V IIN, 50/60 Hz
Weight	Kg	200
Machine Dimensions	mm	Long: 620mm; Large: 610mm; Height: 1160mm
YARN		
Feeding bobbin shape	---	Any kind of shape package
Feeding bobbin dimensions	mm	Max height: 450mm; Max. diameter.: 250mm
Twist range	twists/ metre	Any tiwst between 0-999
FINAL BOBBIN		
Bobbin shape	---	Bobbin of next process.

The technology used in this product is protected by appropriate international patents.



TWISTECHNOLOGY®

FRIMAL TRADING S.L.

Tel. +34 93 789 41 00 • Fax +34 93 789 43 55

e-mail: info@twisttechnology.com

www.twisttechnology.com